



## **GTS Super Sport 300 I-GET – TECHNICAL SPECIFICATIONS**

|                                      |                                                                        |
|--------------------------------------|------------------------------------------------------------------------|
| <b>ENGINE</b>                        | HPE Single cylinder i-get 4-stroke                                     |
| <b>DISPLACEMENT*</b>                 | 278 cc                                                                 |
| <b>BORE X STROKE</b>                 | 75 mm x 63 mm                                                          |
| <b>MAX POWER AT THE CRANK SHAFT*</b> | 17.5 kW @ 8,250 rpm                                                    |
| <b>MAX TORQUE*</b>                   | 26 Nm @ 5,250 rpm                                                      |
| <b>CONSUMPTION*</b>                  | -                                                                      |
| <b>CO2 EMISSIONS COMPLIANCE*</b>     | -                                                                      |
| <b>FUEL SYSTEM</b>                   | Electronic injection PFI (Port Fuel Injection)                         |
| <b>COOLING</b>                       | Liquid                                                                 |
| <b>STARTER</b>                       | Electric                                                               |
| <b>GEARBOX</b>                       | CVT continuously variable transmission with torque server              |
| <b>CLUTCH</b>                        | Automatic centrifugal dry clutch with vibration dampers                |
| <b>LOAD-BEARING STRUCTURE</b>        | Sheet steel body with welded reinforcements                            |
| <b>FRONT SUSPENSION</b>              | Single-sided link arm with coil spring and single shock absorber       |
| <b>REAR SUSPENSION</b>               | Double hydraulic shock absorber with preload adjustable on 4 positions |
| <b>FRONT BRAKE</b>                   | Ø 220 mm stainless steel disc with hydraulic control – ABS             |
| <b>REAR BRAKE</b>                    | Ø 220 mm stainless steel disc with hydraulic control – ABS/ASR         |
| <b>ABS SYSTEM</b>                    | Dual channel ABS                                                       |
| <b>FRONT TYRE</b>                    | Tubeless 120/70 - 12"                                                  |
| <b>REAR TYRE</b>                     | Tubeless 130/70 - 12"                                                  |
| <b>LENGTH / WIDTH / WHEELBASE*</b>   | 1.980 / 795 / 1.380 mm                                                 |
| <b>SEAT HEIGHT*</b>                  | 790 mm                                                                 |
| <b>FUEL TANK CAPACITY*</b>           | 8.5 ± 0.5 litre                                                        |
| <b>EMISSIONS COMPLIANCE</b>          | Depend on market emission standards                                    |

*\*Data may change depending on market homologation*