



GTV 300 I-GET – TECHNICAL SPECIFICATIONS

ENGINE	HPE Single cylinder i-get 4-stroke
DISPLACEMENT*	278 cc
BORE X STROKE	75 mm x 63 mm
MAX POWER AT THE CRANK SHAFT*	17.5 kW @ 8,250 rpm
MAX TORQUE*	26 Nm @ 5,250 rpm
CONSUMPTION*	-
CO2 EMISSIONS COMPLIANCE*	-
FUEL SYSTEM	Electronic injection PFI (Port Fuel Injection)
COOLING	Liquid
STARTER	Electric
GEARBOX	CVT continuously variable transmission with torque server
CLUTCH	Automatic centrifugal dry clutch with vibration dampers
LOAD-BEARING STRUCTURE	Sheet steel body with welded reinforcements
FRONT SUSPENSION	Single-sided link arm with coil spring and single shock absorber
REAR SUSPENSION	Double hydraulic shock absorber with preload adjustable on 4 positions
FRONT BRAKE	Ø 220 mm stainless steel disc with hydraulic control – ABS
REAR BRAKE	Ø 220 mm stainless steel disc with hydraulic control – ABS/ASR
ABS SYSTEM	Dual channel ABS
FRONT TYRE	Tubeless 120/70 - 12"
REAR TYRE	Tubeless 130/70 - 12"
LENGTH / WIDTH / WHEELBASE*	1,975 / 775 / 1,375 mm
SEAT HEIGHT*	790 mm
FUEL TANK CAPACITY*	8.5 ± 0.5 litre
EMISSIONS COMPLIANCE	Depend on market emission standards

**Data may change depending on market homologation*